



GP3 – ELEVATING 4 WAY FLOAT TABLE SYSTEM WITH ROTATE TUBE STAND

Choice of 20, 32, 40 or 50 kW High Frequency Generator

HF Generators


SHF210AP – 320 mA, 125 kVp (250 mA @ 80 kVp), 16 mA Stations
 SHF310AP – 400 mA, 125 kVp (400 mA @ 80 kVp), 17 mA Stations
 SHF410AP – 500 mA, 125 kVp (500 mA @ 80 kVp), 18 mA Stations
 SHF510AP – 640 mA, 125 kVp (640 mA @ 78 kVp), 19 mA Stations

- 0.001 to 10 Second Time Range
- 0.1 to 500 mAs
- kVp Selection, 40 to 125 kVp in 1 kV Increments
- Digital Displays
- Automatic Line Compensation
- APR, Anatomical Programming
- Table Mount Standard, Pedestal Optional
- Exposure Hand Switch
- UL/CE/FDA/Listed
- For Operation on 1 Phase 208/240VAC – 3 Phase Optional
- AEC Optional



Power Cabinet Specifications

Line Powered



MILL-EL-B Elevating Four Way Float Top Table



- Table Top Supports Patients up to 750 lbs. (340 kgs)
- 86.5" x 31.5" (220 x 80 cm) Float Top Table
- 43.4" (110 cm) Longitudinal and 9.5" (24 cm) Lateral Table Top Travel
- 19.7" (50 cm) to 35.5" (90 cm) Vertical Travel
- Magnetic Table Top Locks
- Collision Detector for Table Base
- Bucky with 10:1 Ratio Grid and Heavy Duty Cassette Tray

13-CSM/S225 Rotate Tube Stand

- Floor-to-Wall Mounted
- ±5" Transverse Travel, 360 Column Rotation
- Vertical Travel 13.5" to 76.8" (34 to 195 cm)
- Fits in Ceiling Heights of 93 to 120" (236 to 305 cm)
- Platform Tube Mount, Angulation Dial and Operator Handles
- Magnetic Locks Control Longitudinal, Transverse, Vertical and Tube Rotation
- 75.7" (192 cm) Longitudinal Travel



13-BF7-GC/S109 Wall Stand with Grid Cabinet

- Floor-to-Wall Mounted Column
- Magnetic Locks
- 17 x 17" (43 x 43 cm) Heavy Duty Grid Cabinet with 103 Line, 10:1 Ratio Grid and Cassette Tray
- 9.75" to 72.75 (24.8 to 184.8 cm) Vertical Travel
- Bucky, Various Grids and Tilting Mechanism Optional

E-7239FX X-Ray Tube

- 140,000 Heat Unit
- 1.0 x 2.0 mm Focal Spots
- Other Tubes Optional

CML125-0001-C Collimator

- Manual Collimator
- Laser light cross hairs
- Swivel Mount
- LED light source

10540-25 High Voltage Cables

- 25' (762 cm) Long

Digital Panel Options

- 14" x 17" (35 x 43 cm) tethered or wireless panel
- 17" x 17" (43 x 43 cm) fixed flat panel

TXR • 5481 Skyland Blvd., E • Cottondale, AL 35453

Phone: 205-556-3803 • Fax: 205-556-3824 • 800-897-9729 • www.txr.com • sales@txr.com

Complies with FDA and Product Safety Requirements. • Specifications Subject to Change Without Notice